



F6564030 Black

Tab Floor

Designed by Edward Barber and Jay Osgerby, 2011

9W - 347Im - 2700K - CRI> 90

Floor luminaire providing direct lighting with adjustable head. Body in painted pressofused aluminium. Multi-led diffuser in specially designed PMMA to avoid the Multi Shadow effect and dazzle. Head rotation ±90°.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

EAN	8059607006573
Mounting	Floor
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	9
Lumen Outnut (lm)	347

Physical

Colour	BIack
Length (mm)	240
Cord colour	Black
Net weight (kg)	1.9
Package height (mm)	160
Package width (mm)	330
Package length (mm)	1210
Package volume (m3)	0.06
IP internal	20



Download

Mounting instructions	$\overline{\uparrow}$	PDF
Mounting instructions	$\overline{\uparrow}$	PDF

Photometric Files

LDT / IES



Technical Drawings

2D	⊥ ZIP
3D	⊥ ZIP



20


















https://professional.flos.com/en/global/product/tab-floor-f6564030/

F6564030

Schematic light drawing



Photometric

Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
Extreme cut off	No

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Power supply	Remote included
Dimmable	No
Power supply type	Electronic 24V
Dimming interface	Switch Integrated (Not Dimmable)
Plug type	Type G, Type A, Type C
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D




Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Spare Parts



01. Black plug assembly kit & 24V RF3320100

driver

02. Locking key tool RF13905





RF3320100

Black plug assembly kit & 24V driver

RF13905

Locking key tool