



F1889044 Anodized Champagne

# **Coordinates Module Suspension CLIII**


Designed by Michael Anastassiades, 2020

180W - 10230lm - 2700K - CRI> 90

Coordinates is a lighting system with diffuse light composed of horizontal and vertical luminaries arranged in a bright grid of various shapes and complexities. Each element is made of extruded anodized aluminium with a champagne finish and a diffuser in platinum optical silicone with an integrated LED strip (CRI 95). Each element is powered and supported by an invisible electrical and mechanical connection designed specifically to allow for the composition of the 4 hanging models (S1, S2, S3, S4) with 2.5-m cables. The 'S Module' is also available. Its geometry was designed to be repeated to create large grids for custom installations. Each Coordinates configuration includes its own ceiling rose, whose integrated electronics allow for the use of different dimmer systems: push, 1-10, DALI. In the absence of these systems, the amount of light can be set during installation with the push system included in the rose. The related CI III version is also available for each configuration for installations with a remote power supply.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



## Main specifications

EAN	8059607031162	
Mounting	Suspension	
Environments	Indoor dry location	
Light source type	LED	
Light sources included	Yes	
LED type	LED Module	
Power (W)	180	
Lumen Output (lm)	10230	

## Physical

Colour	Anodized Champagne	
Length (mm)	1770	
Cord colour	Clear	
Cord length (mm)	2400	
Canopy colour	Anodized Champagne	
Canopy length/diameter (mm)	61	
Canopy height (mm)	29	
Net weight (kg)	6	
Package volume (m3)	0.05	
IP internal	20	

Download  Mounting instructions	<b>⊥</b> PDF
Photometric Files	<b>⊥</b> ZIP
Technical Drawings	1. 715
3D ⊕Bim	± ZIP

https://professional.flos.com/en/global/product/coordinates-module-suspension-cliii-f1889044/

F1889044



















### Photometric

Lighting type	Total	
Light distribution	Asymmetric	
CCT (K)	2700	
CRI>	90	
Extreme cut off	No	

### Electrical

Insulation class	III	
Main voltage (Vac)	48	
Power supply	Remote excluded	
Power supply type	Electronic 48V	
Batteries inside	No	

# Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **F** 



Replaceable (LED only) light source by a professional

# **Accessories & Power Supply**





**OPTIONAL** 

RF27617


48Vdc 240W Power supply

**OPTIONAL** 

RF26994

12-48V Led Dimmer

# **Spare Parts**



01.	Assembly Rose Cover for	RF1874144
	Coordinates S CLIII Anodized	
	Champagne	
02.	Coordinates Module CL. III Rod	RF31461
	Assembly L1340 SA-32	
	Champagne	
03.	Coordinates S Rod Assembly	RF30989
	L1340 S-30 Anodized	
	Champagne	
04.	Coordinates S Rod Assembly	RF30988
	L1340 S-29 Anodized	
	Champagne	
05.	Coordinates S Rod Assembly	RF30990
	L1760 H-31 Anodized	

Champagne









#### RF1874144

Assembly Rose Cover for Coordinates S CLIII Anodized Champagne

#### RF31461

Coordinates Module CL. III Rod Assembly L1340 SA-32 Champagne

#### RF30989

Coordinates S Rod Assembly L1340 S-30 Anodized Champagne

#### RE30988

Coordinates S Rod Assembly L1340 S-29 Anodized Champagne

RF30990

Coordinates S Rod Assembly L1760 H-31 Anodized Champagne