

Product information sheet for separate control gear in/with **Audrey Floor**

Supplier name: UIMAGE ApS

Supplier address: Havnegade 29, 1058 Copenhagen Denmark

Model identifier: MKE-1203000DEXD

From April 2025:

Input parameters	AC 100-240V, 50/60Hz, 800mA
Output parameters	DC 12V, 3A Max
Dimming compatible:	No
Compatible dimming control system(s):	N/A
Require external dimmer?	N/A
Recommended external dimmers:	N/A
Maximum output power of the control gear:	36 W
Type of light-source for which this control gear is intended for:	LED
Efficiency in full-load:	88,6 %
No-load power:	0,11 W
Standby power:	0 W
Network standby power:	N/A
Warning:	This control gear must not be used with other products than, the product it came pre-installed with
Outer dimensions:	Height = 71 mm
	Width = 43 mm
	Depth = 43 mm
Weight:	130 g

Model identifier: MKE-1202500DEXD

Before April 2025:

Input parameters	AC 100-240V, 50/60Hz, 800mA
Output parameters	DC 12V, 2,5A Max
Dimming compatible:	No
Compatible dimming control system(s):	N/A
Require external dimmer?	N/A
Recommended external dimmers:	N/A
Maximum output power of the control gear:	30 W
Type of light-source for which this control gear is intended for:	LED
Efficiency in full-load:	88,6 %
No-load power:	0,29 W
Standby power:	0 W
Network standby power:	N/A
Warning:	This control gear must not be used with other products than, the product it came pre-installed with
Outer dimensions:	Height = 71 mm
	Width = 43 mm
	Depth = 43 mm
Weight:	130 g