Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: UMAGE	
--------------------------------------	--

Supplier's address: UMAGE ApS, Havnegade 29, 1058 Copenhagen, DK

Model identifier: 2165 (light-source)

Tvi	рe	of	lig	ht	SO	urce	:
. , ,		•	о		-		•

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	LED Spot				
(or other electric interface)	1,3W 0,4A				
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					
Parameter	Value	Parameter	Value		

1 Todace parameters					
Parameter		Value	Parameter	Value	
		General product p	arameters:		
	mption in on- 100 h), rounded st integer	2	Energy efficiency class	F	
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	125 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode pressed in W	oower (P _{on}),	1,3	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82	
Outer	Height	23	Spectral power	See image	
dimensions	Width	23	distribution in the	in last page	
without	Depth	19	1		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity	0,444		
		coordinates (x and y)	0,414		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	3	Survival factor	1,00		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;

